

# Side Trimmers



## Telescopic Boom with Rubber Tires

- Telescoping composite boom with 75-foot reach from ground. Insulated and tested to ANSI A92.2-2001, Category C
- Cab equipped with 1-1/4-inch tinted Lexgard top for operator protection
- Powered by a 4.4 liter diesel engine rated at 127 hp
- All wheel drive with logger's tires for severe conditions



## Telescopic Boom with Rubber Tracks

- Telescoping composite boom with 75-foot reach from ground. Insulated and tested to ANSI A92.2-2001, Category C
- Cab equipped with 1-1/4-inch tinted Lexgard top for operator protection
- Powered by a 4.4 liter diesel engine rated at 127 hp
- Rubber tracks with a low ground pressure of 3.0 PSI for soft and unimproved conditions

# Side Trimmers



## Skidder with Standard Lift

- 60-foot working height
- 45-foot side reach
- All terrain capability
- Low ground pressure tires



## Skidder with Elevator Lift

- 75-foot working height
- 49-foot side reach
- All terrain capability
- Low ground pressure tires

# Side Trimmers



## “Paddlefoot” or “Bigfoot” 4x4 Platform-Mounted Lift

- 62-foot working height
- Roadside and all terrain capability
- Low ground pressure tires



## Slashbuster with Feller Buncher Attachment

- Excavator mounted on a 25-ton Class machine
- Powered by a 250 hp diesel engine
- Reach capabilities up to 27 feet
- Single cut capacity of 22 inches